

PRODUCT DATA SHEET

CHAIN HOIST 500KG ULTRA LV ACCORDING D8PLUS

Model number basic hoist	CM-960505
Voltage / Frequency	208V / 60Hz
Speed	16 ft/min
Version	contactor control



CHAINMASTER GmbH
Uferstr. 23
04838 Eilenburg | Germany

+49 3423 6922 0
+49 3423 6922 21

info@chainmaster.de
www.chainmaster.de

Table of contents

1. General Description	3
2. Technical Data	4
2.1. Data Sheet	4
Features.....	4
Options/ accessories.....	4
Technical data.....	4
Electrical data	4
3. Dimension Sheet.....	5
3.1. Climbing hoist – single hole suspension plate	5
3.2. Single hole suspension plate & hook suspension.....	6
3.3. Hook tackle	7

List of figures

Figure 1	Climbing hoist – single hole suspension plate	5
Figure 2	Single hole suspension plate & hook suspension	6
Figure 3	Hook tackle	7

Revision administration

Rev.	Date	File name	Author	Description
1.0	05.08.2026	DS_CH_D8PLUS_SK_030-76_500kg_16ft_1f_208V-60Hz_CCAC-24.docx	M.Pohl	Initial creation

Alle Rechte vorbehalten. Dieses Datenblatt ist urheberrechtlich geschützt und Eigentum von CHAINMASTER GmbH.
Die Vervielfältigung, Verbreitung oder anderweitige auch nur auszugsweise Verwertung ist ohne Zustimmung von CHAINMASTER GmbH untersagt.
Abbildungen und Fotos entsprechen Beispielkonfigurationen.

*All rights reserved. This datasheet is protected by copyright and is the property of CHAINMASTER GmbH. Duplication, distribution and other utilization, also in extracts, is not permitted without consent of CHAINMASTER GmbH.
Illustrations and photos correspond to sample configurations.*

Irrtümer und technische Änderungen vorbehalten / Mistakes and technical modifications reserved.

1. General Description

General Description

On the road or fixed installations in studios, halls, theatres and shows – CHAINMASTER chain hoists are worldwide established in the entertainment sector.

Depending on the load case and the combination of CHAINMASTER control systems, extensive projects regarding safety requirements can be fulfilled.

Customized special design for all imaginable cases of application rounds up the world-wide most extensive offer of chain hoists – Made by CHAINMASTER.

According to D8Plus, the chain hoist with 500 kg is equipped with two independently acting brakes, an operating brake and a safety brake. Both brakes are DC brakes. They operate according to the closed-circuit current principle. In the event of a power failure, the brakes apply automatically so that the load is held safely in any position.

The chain hoist is equipped with a sliding clutch, which serves to protect the drive. Electronic overload and underload monitoring can be integrated. It is also possible to limit the highest and lowest load position by means of adjustable operating- and emergency limit switches. Optionally, the chain hoist can be equipped with an incremental encoder, which then enables positioning with millimeter accuracy with the corresponding control.

For the chain hoist a high-strength profile steel chain according to EN818-7 with a hook tackle and a lift limiter as well as a textile chain bag is used. Safe chain entry and exit is ensured by a polyamide chain guide plate.

The robust and compact housing made of cast aluminum alloy is finished with a semi-gloss RAL 9005 (black) paint and is optionally available in other RAL colors. The electric chain hoist is controlled by contactor control in the low voltage range as standard. The operating voltage is 208V, 3ph, 60 Hz.

2. Technical Data

2.1. Data Sheet


Chain hoist 500 kg according D8Plus																															
Features	- completely enclosed aluminum cast housing - black paint finish RAL 9005 – semi gloss (other colors on request) - light and compact design with low- noise running - chain bag made from textile material 2 spring loaded brakes with DC magnet coils - sliding clutch to protect the drive - chain guide plate of polyamide - precise chain guide with 5 - pocket chain sprocket wheel - operating coefficient load chain - 8 (according SQP2 2024-03) 1-fall load hook - standard or climbing hoists - AC-contactor control 1m connection cable 2 handles																														
Options/ accessories	- rotating hook suspension - operational limit switches for upper and lower end (Stromag Geared Cam Limit Switches Series 51 / 51DZ) - emergency limit switches for upper and lower end ³ (Stromag Geared Cam Limit Switches Series 51 / 51DZ) - load monitoring - incremental encoder HTL-signals; 11 / 25 / 100 / 200 / 1024 pulses per revolution - flight cases and storage solutions - manual beam trolley - control systems																														
Technical data	<table> <tr> <td>Model type:</td><td>SK030 / 76</td></tr> <tr> <td>Hoisting speed:</td><td>16 ft/min ¹</td></tr> <tr> <td>Safe working load:</td><td>500 kg</td></tr> <tr> <td>Number of falls:</td><td>1</td></tr> <tr> <td>Load chain according EN 818-7:</td><td>5.4 x 15 mm (profile steel)</td></tr> <tr> <td>Suspension type:</td><td>Single hole suspension eye for shackle</td></tr> <tr> <td>Classification of mechanism lifting gear</td><td>2m/ M5</td></tr> <tr> <td>FEM/ ISO:</td><td></td></tr> <tr> <td>Duty cycle - starts per hour:</td><td>ED 40 % - 240 c/h</td></tr> <tr> <td>Mode of operation:</td><td>S3 (according IEC 60034-1)</td></tr> <tr> <td>Noise level:</td><td>74 dBA/ 1 m distance</td></tr> <tr> <td>Motor type:</td><td>K20R 63G4E</td></tr> <tr> <td>Motor speed:</td><td>1680 rpm ¹</td></tr> <tr> <td>Weight (without chain):</td><td>approx. 21 kg ²</td></tr> <tr> <td>Weight of the chain:</td><td>approx. 0.59 kg/m</td></tr> </table>	Model type:	SK030 / 76	Hoisting speed:	16 ft/min ¹	Safe working load:	500 kg	Number of falls:	1	Load chain according EN 818-7:	5.4 x 15 mm (profile steel)	Suspension type:	Single hole suspension eye for shackle	Classification of mechanism lifting gear	2m/ M5	FEM/ ISO:		Duty cycle - starts per hour:	ED 40 % - 240 c/h	Mode of operation:	S3 (according IEC 60034-1)	Noise level:	74 dBA/ 1 m distance	Motor type:	K20R 63G4E	Motor speed:	1680 rpm ¹	Weight (without chain):	approx. 21 kg ²	Weight of the chain:	approx. 0.59 kg/m
Model type:	SK030 / 76																														
Hoisting speed:	16 ft/min ¹																														
Safe working load:	500 kg																														
Number of falls:	1																														
Load chain according EN 818-7:	5.4 x 15 mm (profile steel)																														
Suspension type:	Single hole suspension eye for shackle																														
Classification of mechanism lifting gear	2m/ M5																														
FEM/ ISO:																															
Duty cycle - starts per hour:	ED 40 % - 240 c/h																														
Mode of operation:	S3 (according IEC 60034-1)																														
Noise level:	74 dBA/ 1 m distance																														
Motor type:	K20R 63G4E																														
Motor speed:	1680 rpm ¹																														
Weight (without chain):	approx. 21 kg ²																														
Weight of the chain:	approx. 0.59 kg/m																														
Electrical data	<table> <tr> <td>Motor power:</td><td>0.37 kW ¹</td></tr> <tr> <td>Power factor cos φ:</td><td>0.71</td></tr> <tr> <td>Nominal voltage:</td><td>3~208 V ¹</td></tr> <tr> <td>Frequency:</td><td>60 Hz</td></tr> <tr> <td>Rated current:</td><td>2.3 A ¹</td></tr> <tr> <td>Safety class:</td><td>I</td></tr> <tr> <td>Degree of protection:</td><td>IP 55</td></tr> <tr> <td>Control equipment:</td><td>AC contactor control</td></tr> </table>	Motor power:	0.37 kW ¹	Power factor cos φ:	0.71	Nominal voltage:	3~208 V ¹	Frequency:	60 Hz	Rated current:	2.3 A ¹	Safety class:	I	Degree of protection:	IP 55	Control equipment:	AC contactor control														
Motor power:	0.37 kW ¹																														
Power factor cos φ:	0.71																														
Nominal voltage:	3~208 V ¹																														
Frequency:	60 Hz																														
Rated current:	2.3 A ¹																														
Safety class:	I																														
Degree of protection:	IP 55																														
Control equipment:	AC contactor control																														

¹ this applies to 60 Hz mains frequency, other voltage levels and frequencies on request


² specification in contactor control, without single-hole suspension eye, hook suspension, hook tackle, chain bag

³ chain hoist is equipped with larger cap

3.2. Single hole suspension plate & hook suspension




Weight: 1.10kg



Weight: 1.85kg


Haken-Nr./ hook-no. DIN 15401	a1	a2	h1	b1	h2	b2
012	30	20	22	19	19	15
025	36	22	28	22	24	19
05	43	28	37	29	31	24
1	50	30	48	38	40	32
2,5	63	42	67	53	58	45
4	71	50	80	63	67	53
6	90	56	100	80	85	67



Diese Zeichnung unterliegt nicht der Revision. Alle Angaben entsprechen dem Stand zum Zeitpunkt der Erstellung. Irrtümer und technische Änderungen vorbehalten.
This drawing is not subject of any revision. All details correspond to the state of technology at the time of construction. Technical modifications reserved.


Figure 2 Single hole suspension plate & hook suspension

3.3. Hook tackle



Weight: 1.05kg

Haken-Nr. / hook-no. DIN 15401	a1	a2	h1	b1	h2	b2
012	30	20	22	19	19	15
025	36	22	28	22	24	19
05	43	28	37	29	31	24
1	50	30	48	38	40	32
2,5	63	42	67	53	58	45
4	71	50	80	63	67	53
6	90	56	100	80	85	67



Diese Zeichnung unterliegt nicht der Revision. Alle Angaben entsprechen dem Stand zum Zeitpunkt der Erstellung. Irrtümer und technische Änderungen vorbehalten.
This drawing is not subject of any revision. All details correspond to the state of technology at the time of construction. Technical modifications reserved.

Figure 3 Hook tackle

This image shows a full page of blank, lined paper. It features approximately 20 evenly spaced horizontal black lines across its entire width, providing a guide for handwriting or typing. The paper is otherwise completely empty, with no margins, text, or other markings.

✉ info@chainmaster.de
 🌐 www.chainmaster.de